

2024 TSSAA Tournament (Team)

BUILT FOR BOWLING

| Oil Pattern Distance | 9 | 45 Reverse E | Brush Drop | 40 | Oil F | Per Board | 5 |
|--|----------------------------|---|--|--------------------------|-------------|----------------------------|----------------------|
| Forward Oil Total | | 14.75 mL Reverse Oil Total | | 10.4 mL Volume Oil Total | | | 25.15 |
| Tank Configuration | <u> </u> | I/A Tank A C | onditioner | Curve | Tanl | B Conditioner | Cı |
| START STOP LOADS ST 1 2L 2R 4 4 2 10L 10R 7 5 3 2L 2R 0 7 3 2L 2R 0 7 4 13L 13R 1 10 | 18 3 A 18 3 A 22 3 A | 148 0.0 7 147 7.6 25 0 25.4 45 0 25.4 5 CROSSED START EN 0 45.0 40 | .6 7.6 7400 .4 17.8 7350 .0 19.6 0 .0 19.6 0 .0 -5.0 0 .3 -18.7 3300 .4 -1.9 650 | | | 10 15 15 15 10 | |
| 5 12L 12R 2 6 11L 11R 2 | 14 3 B 14 3 B | 34 17.5 13 | | | | | |
| 7 10L 10R 2 8 2L 2R 0 | 10 3 B 10 3 B | 42 9.7 6 | i.9 -2.8 2100 0.0 -6.9 0 | | | | |
| | | | | | | | |
| | | | | | | | |
| Cleaner Ratio Main M Cleaner Ratio Back E Cleaner Ratio Back E Buffer RPM: 4 = 720 | nd Mix Ind Distance | NA NA | Forward Reverse Combined | | | | |
| | | | | | | | |
| | 8L-7L:18L-18R | 8L-12L:18L-18R | 13L-17L:18L-18R | | R:17R-13R | 18L-18R:12R-8R | 18L-18R:7R-3R |
| | | | Inside Track:Middle | | nside Track | | Middle:Outside Track |
| rack Zone Ratio | 6.25 | 2.36 | 1.12 | | 1.12 | 2.36 | 6.25 |
| 1350 | | | | | | | |
| 1 2 3 4 | 5 6 7 8 9 | 10 11 12 13 14 15 | 16 17 18 19 29 19 | 18 17 16 | 15 14 13 12 | 1 1 1 1 1 1 1 | 5 4 3 2 1 |